

# CLEANING SEALING & AFTERCARE

## GRIMEX TECHNICAL DATA SHEET

REF: 7/5/1 MARCH 2017



### LTP GRIMEX

#### Heavy Duty Grime Remover For interior & exterior use

Suitable for travertine, limestone, sandstone, slate, marble, porcelain, granite, terracotta, quarry tiles, brick & external paving.

Effective for removing oil, grease, ingrained dirt grime and old wax layers.

**Important:** - Test on an inconspicuous area before general application. Mask and protect painted surfaces, untreated wood and other sensitive areas. Rinse off overspray. Any alkalinity/Grimex remaining on surfaces should be completely neutralised. This may be done with a little clean water applied by sponge.

#### Directions for use

For application and cleaning tools see LTP website.

**In mild cases and on absorbent tiles:**

Dilute one part LTP Grimex in 10 parts warm water. Apply with a cloth or mop. Wipe off thoroughly with a clean damp cloth.

**In more severe cases:**

Dilute one part LTP Grimex in 3 parts warm water. Apply liberally, spreading over surface of tiles. If necessary agitate with a scrubbing brush. Leave to react for 5-10 minutes, keeping wet with additional solution. Agitate surface again, mop up and rinse thoroughly with clean water.

**In extremely severe cases:**

Use undiluted and agitate with scrubbing brush or mechanical scrubber if necessary. Neutralise treated surface with clean water after use.

#### Coverage

Per Litre

In mild cases - approximately 50m<sup>2</sup>

In more severe cases - approximately 20m<sup>2</sup>

In extremely severe cases - approximately 5-10m<sup>2</sup>

#### Storage information

Store in a cool, dry, frost-free environment in closed container. Shelf life up to 5 years.

#### Notes:

This product should not be used for every day cleaning of floors or walls that have been sealed.

Cleaned surfaces that have been previously sealed should be re-sealed after using this product. This should be done after rinsing with plenty of clean water and once surfaces have had sufficient time to thoroughly dry (min 24hrs).

#### Health, Safety & Environmental

**Causes skin irritation. Causes serious eye irritation**

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Wash hands thoroughly after handling. Wear protective gloves and eye protection. IF ON SKIN: Wash with plenty of water/soap. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. Dispose of contents/container in accordance with local regulations.

**WARNING**



**Contains:** <5% non ionic surfactants, phosphates.

Ingredients: [www.ltp-online.co.uk/dr](http://www.ltp-online.co.uk/dr)

Contains: 2-BUTOXYETHANOL-TETRAPOTASSIUM PYROPHOSPHATE-(L) C9-11 PARETH-9, AMMONIA SOLUTION



This information is offered without guarantee.

The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline  
+44 (0) 1823 666213 | [www.ltp-online.co.uk](http://www.ltp-online.co.uk) | [info@ltp-online.co.uk](mailto:info@ltp-online.co.uk)  
Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN UK

